







Easy as 1, 2, 3!

- 1 Add 1mL of sample to the first Dilucup®
- 2 Shake to mix the dilution
- 3 Transfer 1mL to the next Dilucup®

The Dilucup® system allows standardization of the dilution process and reduces variability.

LED lights indicate the position of the next dilution reducing errors




Dilucup® Elegance

Dilucup® Elegance is a small container pre-filled with 9 mL of sterile diluent.

Choice of Maximum Recovery Diluent, Buffered Peptone Water or Saline

A thin film guarantees the sterility and **right volume** in the cups.





Dilucup® System

SAVE TIME

Reduces technician labor time and cost; allows them to reallocate saved time to other activities









Specifications	Dilushaker III	Dilugent® Shaker
Shaking tim	1 to 30 s	1 to 60 s
Motor speed	400, 500, 600 rpm	410, 460, 510, 560, 610, 660 rpm
Number of LED lights	3 or 6	42
Steering by footswitch	Yes	Yes
Opti al sensor for shaking	One in the front	Two; one on each side
Total height (without screen)	11 cm	8 cm (more ergonomic)
Tray removal	Rotate while pressing	Magnetic
Same machine for 7x3 or 7x6 Dilucups®	No	Yes
Traceability of dilution	No	Yes*
Shake without influencing the LED lig ts	No	Yes
Simultaneous dilution with o ti al guide	No	Yes

^{*} Not available with Dilugent® Shaker Light



Dilushaker III	
Tray for 21 Dilucups® (7x3), ramp with 3 LED lights. 19cm x 34.5cm x 11.5cm	40DS21PRXT
Tray for 42 Dilucups® (7x6), ramp with 3 LED lights. 26cm x 34.5cm x 11.5cm	40DS42PRXT
Dilugent® Shaker <i>Light</i>	
Same design with a lighter soft are. No traceability.	40DGT84LT
Dilugent® Shaker	
Traceability of dilutions. xport of information. 2 code reading with external scanner.	40DGT84SD
Dilugent® Shaker <i>Pro</i>	
Advanced programming for those who work with duplicates, triplicates or have other traceability needs. Possible connection o LIMS.	40DGT84PO 13